THE CHRONOTRACK PRO 2 CONTROLLER

ATHLINKS SERVICES

KEEPING YOUR CONTROLLERS IN THE FIELD AND AHEAD OF THE CURVE

Timing technology is changing more rapidly than ever before. The Pro 2 controller was built with a modular approach on a hardware and software foundation that will allow ChronoTrack to keep pushing the industry forward without forcing our customers to replace controllers every few years to keep up. This means you get new features faster and in a more cost-effective way.

TOP 10 REASONS YOU'LL LOVE THE NEW PRO 2 CONTROLLER AND IT'S MODULAR DESIGN

1 Easily stay ahead of your competition by adding on new (or updating existing) modules yourself in the field.

2 Keep controllers out in the field more often and keep updating/fix costs down with self-service module changes.

3 New software – we've interviewed timers and organized the user interface in a manner that's simpler and easier to use.

4 Operating on Ryobi batteries means you can stock up on batteries at Home Depot for a fraction of the cost of the custom-made batteries of the past.

5 Use touchscreen or keypad to input event information. Both are always options.

6 Take off your glasses and don't worry about fat fingers. Now there's more screen space and increased display resolution.

7 Modular circuit board design: if something breaks or we provide an upgrade, less components will need to be replaced reducing cost.

8 Head unit of the Pro 2 can easily be replaced in the field.

9 All controllers have built in port to provide additional functionality. General Purpose inputs and an aux port are standard out of the box.

10 ChronoTrack can innovate more quickly with the new Linux-based OS that allows for more flexibility with software changes.

HOW THE PRO 2 CONTROLLER COMPARES TO THE PRO SERIES CONTROLLER

PERFORMANCE	SPEFIFICATIONS	NOTABLE DIFFERENCES
Same		
DISPLAY/INPUT DEVICE		
Interface Type	5" (12.7 cm) Touchscreen	Pro series is 4.75"W x 3.25"H (12.07 x 8.26cm)
19 Button Keypad	Touch panel computer on pro series	
Display Size	800x480 pixel	
LED Display	Dual color, 50Wx7H LED display (marquee on front)	
Gun Start	Mechanical	
COMMUNICATIONS		
LAN	2 Ethernet ports	
WiFi	Built-in	
Cellular	Built-in cellular	
PORTS		
Antenna	8 ports with status lights	No 4-port option now
USB	3 2.0 ports	1 additional USB port
Auxilary Port	Support for add-on devices (Active Extension), ability to provide 12v power to other devices	Add-on device support new
AUDIO		
Buzzer	107 dB with rotary volume control	No 4-port option now
POWER		
Total Battery Ports	5: 4 external, 1 internal	
Hot-Swappable, Lockable Ports	4 external	Current Pro is not hot-swappable and all batteries are internal
Operates on AC power	Yes	
Will Charge on AC Power; Powered Off	Yes	
Recommended Battery	Ryobi P108	
DATA MANAGEMENT		
Data Exportable Through	USB thumb drive, LAN, WiFi & cellular connections	
PHYSICAL SPECS		
Weight	32 lbs. (14.5kg) with batteries, 24 (10.8kg) without	Similar weight with batteries to the 800 series controller
External Dimensions	20.75" x 17.5" x 8.5" (52.71 x 44.45 x 21.59cm)	
Lid Props	Yes	
INTERROGATOR (GATOR) CAPABILITY		
All		
CHRONOTRACK TAG COMPATIBILITY		
All		
WARRANTY		
Same		
STORAGE		
Storage slot	For power adapter, not physically connected	New
Storage pocket	For future potential modifications/add-ons	New

TO REQUEST MORE INFORMATION ON THE PRO 2 CONTROLLER, CONTACT US AT (855) 709-4555 OR INFO@ATHLINKS.COM, INFORMATION OR REQUEST MORE INFORMATION AT ATHLINKS.COM/SERVICES